

Section 1: Identification of the Product/Company

Product Identifier:

Product Name: VERSA LOOK POLY SEAL (PART A) Product Code: 150 A

Relevant identified uses of the substance or mixture

Recommended use:

For professional use in the construction industry

Uses advised against:

Keep away from children

Details of the supplier of the safety data sheet Manufacturer:

Super Stone Inc. 1251 Burlington Street Opa-Locka, FL 33054 United States <u>www.superstone.com</u> (305) 681-3561

Telephone (General)

Emergency telephone number

 Manufacturer:
 (800) 424-9300 (Chemtrec)
 USA

 + 1 (703) 527-3887 (Chemtrec) International

Section 2: Hazards Identification

Classification of the substance or mixture GHS-US classification

Skin irritation: Skin sensitization: Eye irritation: Category 2, H315 Category 1, H317 Category 2B, H320

Page **1** of **12**



Label elements GHS-US labeling

The substance is classified and labeled according to the Globally Harmonized System (GHS). Hazard Pictograms (GHS-US)



Warning
H315 Causes skin irritation H317 May cause an allergic skin reaction H320 May cause eye irritation
P101 If medical advice is needed, have product container or label on hand P102 Keep out of reach of children P103 Read label before use P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray P280 Wear protective gloves, clothing, and eye/ face protection
P305+P351+P338 IF in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label) Page 2 of 12



P363 Wash contaminated clothing before reuse

Storage:

Disposal:

P501 Dispose of contents and containers in accordance with local, regional and international regulations

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)-Annex III

Other hazards

The substance/mixture does not meet the PBT/vPvB criteria of REACH, annex XIII

Unknown acute toxicity (GHS-US)

No data available

Section 3: Composition/information on ingredients

Substances

Name	Product Identifier	% by weight	GHS-US classification
Mixture of biocides	CAS # 55965-84-9	0-10	Skin sensitizer 1, H317
	EC # combination		Skin irritant 2, H315
	247-500-7 & 220-239-6,		Eye irritant 2B, H320
Anionic Polyacrylate	CAS # 52880-57-6	25-50	

Amounts specified are typical and do not represent a specification. Any other ingredients are either proprietary, non-hazardous or present in amounts below the reportable limits.



Section 4: First aid measures

Description of necessary first aid measures

First-aid measures general:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: consult doctor/ hospital. Never give alcohol to drink.

First-aid measures after inhalation:

Supply fresh air and to be sure call for a doctor. In case of unconsciousness, place patient stably in side position for transportation.

First-aid measures after skin contact:

Immediately wash with water and soap and rinse thoroughly

First-aid measures after eye contact:

Remove contact lenses if able to do so. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

First-aid measures after ingestion:

A person vomiting while lying on their back should be turned onto their side. Do not induce vomiting; immediately call for medical help. If symptoms persist, consult doctor.

Most important and effects, both acute and delayed

Allergic reactions, nausea, gastric and intestinal disorders

Indication of any immediate medical attention and special treatment needed

Treat skin and mucous membrane with antihistamine and corticoid preparations.

Section 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

Unsuitable extinguishing media:

Page **4** of **12**



None specified **Special hazards arising from the substance or mixture** No further relevant information available

Advice for firefighters

Firefighting instructions:

Precautionary measures fire

No special measures required

Additional information

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures Not required

Environmental precautions

Dilute with plenty of water. Do not allow to enter sewer/ surface or ground water

Methods and material for containment and cleaning up. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protective equipment See Section 13 for disposal information

Section 7: Handling and storage

Precautions for safe handling

Additional hazards when processed:

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Conditions for safe storage, including any incompatibilities

Technical measures:

No special requirements

Storage conditions:



Keep receptacle tightly sealed Incompatible products: Store away from foodstuff Incompatible materials:

Do not store with oxidizing and acidic materials

Storage area:

The product should be stored in a cool, dry and well ventilated area, at ambient temperature directly out of the sunlight.

Specific end use(s)

No further relevant information available

Section 8: Exposure controls/personal protection

Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace

Occupational exposure limits:

Exposure controls

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Page **6** of **12**



Neoprene gloves, Nitrile rubber, NBR, PVC or PE gloves, Rubber gloves


The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and therefore has to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials

Strong gloves and leather gloves **Eye protection:**



Body protection: Apron

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	
Color:	White
Odor:	Acrylic
Odor threshold:	Not determined
pH:	Not determined
Relative evaporation rate (butyl acetate=1):	Not determined
Boiling Range:	199° F
Melting point:	Undetermined
Auto-ignition temperature:	Product is not self-igniting
Decomposition temperature:	Not Determined
Flammability (solid, gas):	Not Applicable
Vapor pressure:	Not Determined
Flash Point:	>199° F
Relative vapor density @ 20 ° C:	Not determined



Relative density: Density: Solubility: Log Pow: Log Kow: Viscosity, kinematic: Viscosity, dynamic: Explosive properties: Oxidizing properties: Explosive limits: 1.0 8.345 lbs / gal Fully miscible Not determined Not determined Not determined Not determined Not applicable None known Not applicable

Other information:

No further relevant information available

Section 10: Stability and reactivity

Reactivity

Reacts with Isocyanates, strong acids and oxidizing agents.

Chemical Stability

Product is stable under normal storage conditions

Conditions to Avoid

No further relevant information available

Incompatible Materials

No further relevant information available

Hazardous Decomposition Products

Carbon Monoxide and Carbon Dioxide

Section 11: Toxicological information

Information on toxicological effects

TOXICITY MEASURES:

Chemical Name	LD50/LC50
Mixture of biocides	Oral LD50: Rat >2,000-10,000 mg/kg
	Dermal LD50: Rabbit >5,000 mg/kg
	Inhalation LC50: Rat 5 mg/ L / 4h



Skin corrosion/irritation: Irritant to skin and mucous membrane
Serious eye damage/irritation: Irritating effect on the eye
Respiratory or skin sensitization:
Sensitization possible through the skin
Germ cell mutagenicity:
This product presents positive results of mutagenicity in in vitro studies.
Carcinogenicity:
There are in vivo studies that indicate positive results of kidney cancer

Section 12: Ecological information

All work practices must be aimed at eliminating environmental contamination.

Toxicity

No further relevant information available

Persistence and degradability

No further relevant information available

Bio-accumulative potential

No further relevant information available

Mobility in soil

No further relevant information available

Other adverse effects

No further relevant information available

Section 13: Disposal considerations

Waste treatment methods

Regional legislation (waste):

Dispose of unused contents (incineration) in accordance with national and local regulations. **Waste disposal recommendations:**



Do not dispose with regular household garbage. Do not allow product to reach sewage system. Ensure the use of properly authorized waste management companies where appropriate.

Section 14: Transport information

In accordance with ICAO/IATA/DOT/TGD Land transport Department of transportation (DOT): Not regulated for transport

Transport by sea Not regulated for transport

Air transport INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): Not regulated for transport

Section 15: Regulatory information

U.S. Federal Regulations

U.S. OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations

U.S SARA Reporting Requirements:

The following components of this product are subject to reporting requirements of sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

CHEMICAL	SECTION 302 EHS (TPQ)	SECTION 304 RQ	SECTION 313 TRI
	(40 CFR 355, Appendix A)	(40 CFR Table 302.4)	(40 CFR 372.65)
Mixture of biocides	No	No	No

SARA Section 311/312 (40 CFR 370) Hazard Categories:

ACUTE: Yes; CHRONIC: No; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No **Toxic Substances Control Act (TSCA)**:

Page **10** of **12**



All components of this product are included on the TSCA inventory **U.S. CERCLA Reportable Quantity (RQ):** Not subjected to reporting requirements

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product does not contain any chemicals known to the State of California to cause cancer or developmental harm.

European Inventory of Existing Chemicals (EINECS):

All of the components of this product are included on EINECS.

Section 16: Other information

Indication of changes: Other information: Full text of H phrases:



NFPA health hazard: 2-Moderately toxic or hazardous material which require additional PPE or equipment than safety goggles and gloves.

NFPA fire hazard: 1-Materials that require considerable pre-heating, under all ambient temperature conditions, before ignition and combustion can occur.

NFPA reactivity: 0-Normally stable, even under fire exposure conditions, and not reactive with water

Notice to Reader

The information provided herein is believed to be accurate at the time of preparation or prepared from sources deemed to be reliable, but it is the full responsibility of the user to

Performed: 03-07-2016

Page **11** of **12**



investigate and comprehend other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. **Super Stone Inc. makes no warranty, expressed or implied, concerning the product or merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by Super Stone Inc.**, except that the product shall conform to Super Stone's specification.



Section 1: Identification of the Product/Company

Product Identifier: Product Name: VERSA LOOK POLY SEAL (PART B) Product Code: 150 Part B

Relevant identified uses of the substance or mixture

Recommended use:

For professional use in the construction industry

Uses advised against:

Keep away from children

Details of the supplier of the safety data sheet Manufacturer:

Super Stone Inc. 1251 Burlington Street Opa-Locka, FL 33054 United States <u>www.superstone.com</u> (305) 681-3561

Telephone (General)

Emergency telephone number

 Manufacturer:
 (800) 424-9300 (Chemtrec)
 USA

 + 1 (703) 527-3887 (Chemtrec) International

Section 2: Hazards Identification

Classification of the substance or mixture GHS-US classification

Acute toxicity: Oral Skin irritation: Skin sensitization: Category 4, H302 Category 2, H315 Category 1, H317

Page **1** of **13**



Serious eye damage: Acute toxicity: Inhalation Sensitization: Respiratory STOT SE 3 Category 2A, H319 Category 3, H331 Category 1, H334 Category 3, H335

Label elements

GHS-US labeling

The substance is classified and labeled according to the Globally Harmonized System (GHS). **Hazard Pictograms (GHS-US)**



Signal words (GHS-US):

Danger

Hazards statements (GHS-US):

H302 Harmful if swallowed H315 Causes skin irritation H317 May cause an allergic skin reaction H319 Causes serious eye irritation H331 Toxic if inhaled H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled H335 May cause respiratory irritation

Precautionary statements (GHS-US) Prevention:

P101 If medical advice is needed, have product container or label on handP102 Keep out of reach of childrenP103 Read label before use



P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray P284 Wear respiratory protection

 Response:
 P305+P351+P338 IF in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P321 Specific treatment (see on this label)

 Storage:
 P405 Store locked up

 Disposal:
 P501 Dispose of contents and containers in accordance with local regional and international

accordance with local, regional and international regulations

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS)-Annex III

Other hazards

The substance/mixture does not meet the PBT/vPvB criteria of REACH, annex XIII

Unknown acute toxicity (GHS-US)

No data available

Section 3: Composition/information on ingredients

Substances

Name	Product Identifier	% by weight	GHS-US classification
Homopolymer of	CAS # 28182-81-2	50-100	Skin sensitizer 1, H317
Hexamethylene Dilsocyanate	EC #		Eye irritant 2A, H319

Page **3** of **13**



Hexamethylene Dilsocyanate	CAS # 822-06-0	<2.5	Acute toxicity 4, H302
	EC # 212-485-8		Skin sensitizer 1, H317
			Respiratory sensitizer, H334
			Skin irritant 2, H315
			Eye irritant 2A, H319
			STOT SE 3, H335

Amounts specified are typical and do not represent a specification. Any other ingredients are either proprietary, non-hazardous or present in amounts below the reportable limits.

Section 4: First aid measures

Description of necessary first aid measures

First-aid measures general:

Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident.

First-aid measures after inhalation:

Supply fresh air and to be sure call for a doctor. In case of unconsciousness, place patient stably in side position for transportation. Move to an area free from further exposure. Extreme asthmatic reactions that may occur in sensitized persons can be life threatening. GET MEDICAL ATTENTION IMMEDIATELY! Administer oxygen or artificial respiration as needed. Asthmatic symptoms may develop and may be immediate or delayed up to several hours.

First-aid measures after skin contact:

Immediately wash with water and soap and rinse thoroughly

First-aid measures after eye contact:

Remove contact lenses if able to do so. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

First-aid measures after ingestion:

A person vomiting while lying on their back should be turned onto their side. Do not induce vomiting; immediately call for medical help. If symptoms persist, consult doctor.

Most important and effects, both acute and delayed

Allergic reactions, nausea, gastric and intestinal disorders

Information for doctor



Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic/steroid preparation as needed. Workplace vapors could produce reversible corneal epithelial edema impairing vision. Skin: This compound is a skin sensitizer. Treat symptomatically as for contact dermatitis or thermal burn. Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of the compound. Inhalation: Treatment is essentially symptomatic. An individual having a dermal or pulmonary sensitization reaction to this material should be removed from further exposure to any isocyanate.

Danger

Danger of impaired breathing and pulmonary edema

Indication of any immediate medical attention and special treatment needed

Later observation for pneumonia and pulmonary edema. Treat skin and mucous membrane with antihistamine and corticoid preparations. Medical supervision for at least 48 hours. Severe allergic skin reaction, bronchial spasms and anaphylactic shock are possible.

Section 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

Unsuitable extinguishing media:

None specified

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire. Exposure to heated diisocyanate can be extremely dangerous.

Advice for firefighters

Firefighting instructions:

Avoid contact with product. Decontaminate equipment and protective clothing prior to re-use. During a fire, isocyanate vapors and other irritating, highly toxic gases may be generated by thermal decomposition or combustion.

Protective equipment:

Wear self-contained respiratory protective device and a fully protective suit.

Precautionary measures fire



Do not inhale explosion gases or combustion gases

Additional information

Use cold-water spray to cool off fire-exposed containers to minimize risk of rupture

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Implement site emergency response plan. Evacuate non-emergency personnel. The magnitude of the evacuation depends upon the quantity released, site conditions, and the ambient temperature. Isolate the area and prevent access of unauthorized personnel. Notify management. Call CHEMTREC at 1-800-424-9300 for assistance and advice

Environmental precautions

Dilute with plenty of water. Do not allow to enter sewer/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system

Methods and material for containment and cleaning up.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Use an isocyanate decontaminating solution such as available from Colorimetric Laboratories, Inc. (CLI): 1-847-803-3737.

Note: Always wear proper PPE when cleaning up an isocyanate spill and using a neutralization solution. It may take two or more applications of the neutralization solution to decontaminate the surface. Check for residual surface contamination using a surface wipe method such as the CLI Swype R pad.

Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protective equipment

See Section 13 for disposal information

Section 7: Handling and storage

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Information about protection against explosions and fires:

No special measures required.

Conditions for safe storage, including any incompatibilities

Page 6 of 13



Storage temperature: Minimum: 7 C (44.6 F) Maximum 50 ° C (122 ° F) Storage: ...

• Requirements to be met by storerooms and receptacles: Store in a cool location.

• Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep receptacle tightly sealed

Section 8: Exposure controls/personal protection

Control parameters

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace

Occupational exposure limits:

Exposure controls


General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

Neoprene gloves, Nitrile rubber, NBR, PVC or PE gloves, Rubber gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and therefore has to be checked prior to the application.

Page **7** of **13**




Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not suitable are gloves made of the following materials

Strong gloves and leather gloves

Eye protection:



Body protection: Impervious protective clothing **Limitation and supervision of exposure into the environment**

Medical Surveillance

All applicants who are assigned to an isocyanate work area should undergo a pre-placement medical evaluation. A history of eczema or respiratory allergies such as hay fever, are possible reasons for medical exclusion from isocyanate areas. Applicants who have a history of adult asthma should be restricted from work with isocyanates. Applicants with a history of prior isocyanate sensitization from further work with isocyanates. A comprehensive annual medical surveillance program should be instituted for all employees who are potentially exposed to diisocyanates. Once a worker has been diagnosed as sensitized to any isocyanate, no further exposure can be permitted.

Additional Protective measures:

Emergency showers and eye wash stations should be available. Educate employees in the safe use and handling of this product. Follow all label instructions.

Page 8 of 13

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	Liquid
Appearance:	Lightly viscous
Color:	Yellow
Odor:	Acrylic
Odor threshold:	Not determined
pH:	Not determined
Relative evaporation rate (butyl acetate=1):	Not determined



Boiling Range: Melting point: Auto-ignition temperature: **Decomposition temperature:** Flammability (solid, gas): Vapor pressure: **Flash Point:** Relative vapor density @ 20 ° C: **Relative density: Density:** Solubility: Log Pow: Log Kow: Viscosity, kinematic: Viscosity, dynamic: **Explosive properties: Oxidizing properties: Explosive limits:**

199° F Undetermined 445 ° C (833 ° F) 181 ° C (358 ° F) Not Applicable 52 mm Hg (68 ° F) 365 ° F Not determined 1.15 9.597 lbs / gal Not miscible Not determined Not determined Not determined Not determined No explosion hazard present None known Not applicable

Other information:

No further relevant information available

Section 10: Stability and reactivity

Reactivity

Reacts with powdered metals and strong oxidizing agents. Reacts with alcohols, amines, aqueous acids and alkalis, copper and copper alloys. Decomposes with water, acids and alkalis. <u>Chemical Stability</u> Product is stable under normal storage conditions <u>Conditions to Avoid</u> No further relevant information available <u>Incompatible Materials</u> No further relevant information available <u>Hazardous Decomposition Products</u>

Performed: 03-11-2016

Page **9** of **13**



Poisonous gases and vapors (Isocyanate), Hydrogen Cyanide, Nitrogen Oxides, Carbon Monoxide and Carbon Dioxide

Section 11: Toxicological information

Information on toxicological effects TOXICITY MEASURES:

Chemical Name	LD50/LC50
Hexamethylene Di-Isocyanate	Oral LD50: Rat 738 mg/kg
	Dermal LD50: Rat 593 mg/kg

Skin corrosion/irritation:

Irritant to skin and mucous membrane

Serious eye damage/irritation:

Irritating effect on the eye

Respiratory or skin sensitization:

May cause skin irritation with symptoms of reddening, itching and swelling. Can cause sensitization. Persons previously sensitized can experience allergic skin reaction with symptoms of reddening, itching, swelling, and rash. Cured material is difficult to remove. Sensitization possible through inhalation.

Carcinogenicity:

No indication of being

Section 12: Ecological information

All work practices must be aimed at eliminating environmental contamination.

Toxicity

Harmful to fish. No further relevant information available

Persistence and degradability

No further relevant information available

Bio-accumulative potential

No further relevant information available

Mobility in soil

No further relevant information available

Page **10** of **13**



Other adverse effects

Self- assessment indicates hazardous for water. No further relevant information available

Section 13: Disposal considerations

Waste treatment methods

Regional legislation (waste):

Dispose of unused contents (incineration) in accordance with national and local regulations.

Waste disposal recommendations:

Do not dispose with regular household garbage. Do not allow product to reach sewage system. Ensure the use of properly authorized waste management companies where appropriate.

Section 14: Transport information

In accordance with ICAO/IATA/DOT/TGD

Land transport

Department of transportation (DOT):

Not regulated for transport

When in individual containers of less than product RQ (Reportable Quantity), this material ships as non-regulated. For quantities greater than the RQ, Land Transport per DOT requires Class 9, UN/NA number 3082, PG III.

Quantity limitations

RSPA/DOT Regulated components:

Hexa-Methylene Di-Isocyanate

Reportable Quantity: 9074 kg (20005 lb)

Transport by sea

Not regulated for transport

Air transport

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA):

Not regulated for transport

Section 15: Regulatory information

Page **11** of **13**



U.S. Federal Regulations

U.S. OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations

U.S SARA Reporting Requirements:

The following components of this product are subject to reporting requirements of sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act.

CHEMICAL	SECTION 302 EHS (TPQ)	SECTION 304 RQ	SECTION 313 TRI
	(40 CFR 355 <i>,</i> Appendix A)	(40 CFR Table 302.4)	(40 CFR 372.65)
HMDI	No	No	No

SARA Section 311/312 (40 CFR 370) Hazard Categories:

ACUTE: Yes; CHRONIC: Yes; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

Toxic Substances Control Act (TSCA):

All components of this product are included on the TSCA inventory

U.S. CERCLA Reportable Quantity (RQ):

Not subjected to reporting requirements

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):

This product does not contain any chemicals known to the State of California to cause cancer or developmental harm.

European Inventory of Existing Chemicals (EINECS):

All of the components of this product are included on EINECS.

Section 16: Other information

Indication of changes: Other information:

Full text of H phrases:

|--|



Page **12** of **13**



NFPA health hazard: 2-Moderately toxic or hazardous material which require additional PPE or equipment than safety goggles and gloves.

NFPA fire hazard:0-Not combustibleNFPA reactivity:0-Normally stable, even under fire exposure conditions, and not reactive withwater-Normally stable, even under fire exposure conditions, and not reactive with

Notice to Reader

The information provided herein is believed to be accurate at the time of preparation or prepared from sources deemed to be reliable, but it is the full responsibility of the user to investigate and comprehend other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. **Super Stone Inc. makes no warranty, expressed or implied, concerning the product or merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided by Super Stone Inc.**, except that the product shall conform to Super Stone's specification.