

MATTING AGENT



Super Stone® Matting Agent is a flattening additive for Super Stone solvent based sealers. This highly effective matting agent provides a variety of finishing options for Super Stone pigmented and clear sealers. Super Stone® Matting Agent allows you to control the shine of your top coat based on the amount of additive used providing options ranging from Satin, Eggshell, to Flat.

RECOMMENDED USAGE

- Super Stone Clear & Pigmented Solvent-Based Sealers

ADVANTAGES

- Effectively reduces gloss
- Produces uniform films
- Improves settling and mar resistance

STORAGE/SHELF LIFE

When stored in the original, tightly closed container, preventing the accumulation of water, dirt or other contaminants, the shelf life is one year from the date of purchase. Store in cool ventilated place. Protect material from direct sunlight.

MIXING RATIOS

Desired Finish	Matting Agent	Sealer
Satin	1.6 ounces	1 Gallon
	½ pound	5 Gallons
Eggshell	2.4 ounces	1 Gallon
	¾ pound	5 Gallons
Flat	3.2 ounces	1 Gallon
	1 pound	5 Gallons

APPLICATION

Mechanically mix in Super Stone® Matting Agent using a low or variable speed drill with a jiffy mixer, at a low speed, until all material is dispersed. If material is allowed to sit, re-mix before use. Various levels of gloss reduction can be achieved by varying the amount of Matting Agent used. Apply sealer according to the Super Stone® Sealer Technical Data Sheet.

LIMITATIONS

Super Stone® Matting Agent should not be used in water-based sealers. It is recommended to perform a test by applying sealer with Super Stone® Matting Agent in an inconspicuous area and allow to dry to verify desired effect. Due to various levels of gloss reduction that can be achieved, mixing/application of this product is at the installer's discretion.

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended and use gloves to avoid repeated contact with the skin. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes. **Skin**-- Wash the affected area thoroughly with soap and water. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If symptoms persist or develop, seek medical attention. **Ingestion**-- Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water. Get medical attention.

Limited Warranty: *Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Super Stone solely and expressly warrants that this product shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective and this shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach.* **NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits. Any installation of Super Stone products which fails to conform with such installation information or instructions shall void this warranty. Buyer shall be solely responsible for determining the suitability of Super Stone's products for the Buyer's intended purposes.**

For Professional Use

DANGER!

OVEREXPOSURE MAY CAUSE EYES, SKIN, AND RESPIRATORY IRRITATION. HARMFUL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN.

