

RELEASE POWDER



Super Stone® Powder Release is a clear or pigmented water repellent powder material that forms a moisture barrier between stamping tools and fresh concrete, facilitating the release of mats. It is a dry shake material applied directly on top of the Color Hardener prior to stamping.

APPLICATION

Release agent is to be applied only after troweling has been completed and after all water has left the surface. The desired spread rate of the release powder is 30lbs every 1,000ft². The use of a dusk mask is required to prevent inhalation. Before broadcasting the release, turn pail upside down and roll it to fluff material.

To determine the time to apply Release: Using your fist, roll your knuckle on the surface of the colored concrete. When none of the colored concrete comes off on your fist, broadcast the release powder evenly over the concrete surface when you are going to place the next few mats. In order to ensure even coloring, try to use the same amount of Release Powder over the complete installation.

Finishing

After 3-4 days, remove the release powder with a pressure washer with approximately 2500 psi. Starting with lower pressure, remove the excess release color without washing it off completely. Washing off the grout lines and deeper indentations with a quicker action than the highlights will allow the darker color release to remain and increase your antiquing effect. Super Stone® Clear Concrete Sealer must be applied after pressure washing when the concrete is thoroughly dried.

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended and use gloves to avoid repeated contact with the skin. Avoid breathing dust. Do not use near fire or flame. Avoid contact with eyes, skin, and clothing. In case of contact with eyes, flush eyes with water for a minimum of 10 min. In case of contact with **skin**, Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. If **ingested**, Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water and give plenty of water to drink. Get medical attention immediately. If **inhaled**, remove to fresh air. Get medical attention if irritation persists or any discomfort, coughing or other symptoms continue or do not subside.

Limited Warranty: *Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits.*

For Professional Use

DANGER! HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN.
MAY CAUSE CANCER AND DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED
EXPOSURE IF INHALED.

