

CONCENTRATED CONCRETE SEALER



Super Stone® Concentrated Concrete Clear Sealer 53% Solids is a solvent-based acrylic sealer available in clear. It is designed for all masonry surfaces. It is a concrete coating that allows superior resistance to automotive grease, oil, and food spills.

RECOMMENDED USAGE

- Stamped Concrete Surfaces
- Super Surface® Overlay System
- Super Tex Wet & Ready®
- Unpainted/Unsealed Concrete
- Brick & Masonry

ADVANTAGES

- Highly Resistant to Water, Alkali, Abrasion & Ultra Violet Rays
- Durable & Aesthetically Appealing
- Minimizes shipping & storage costs

COVERAGE

1 Gallon Covers Approximately 150 ft²
5 Gallons Cover Approximately 750 ft²

DRY TIME

24 hours for foot traffic
72 hours for vehicular traffic

SURFACE PREPARATION

Before applying Super Stone® Concentrated Concrete Sealer, make sure all contaminants and bond-inhibiting materials are removed from the surface. Use Super Stone® Cleaner/ Degreaser to remove dirt, oil, and other petroleum based contaminants. Use Super Stone® Strip It Off to remove old acrylics, epoxies, and polyurethanes. Failure to remove contaminants will result in adhesion loss, reduced durability, or peeling. After cleaning, the surface must be allowed to dry completely or moisture may become trapped beneath the sealer resulting in peeling. Concrete must be fully cured.

APPLICATION

Super Stone® Concentrated Concrete Sealer is cut with Super Stone® Solvent (xylene). Sealer may be applied with a brush, a ¼"-¾" nap roller, or a sprayer resistant to solvents. For best results, apply sealer in a thin, even coat when surface and ambient temperatures are above 50° F (10° C). Let the first coat dry for 2-4 hours depending on humidity and repeat the procedure until desired results are achieved. Two thin coats are recommended. Do not allow the product to puddle or collect in joints. Caution should be taken on non-textured surfaces as the end result can produce a surface that is slippery. Blending Super Stone® Super Grip® in the final coat of sealer gives the surface a Coefficient of Friction of 0.7 according to ASTM D 2047-93. Clean tools with Super Stone® Solvent (xylene).

LIMITATIONS

Super Stone® Concentrated Concrete Sealer should not be used in areas subject to:

- Water Submersion
- Significant Chemical Exposure
- Concentrated Abrasion/Scratching
- Metal Wheel Traffic
- Roadways

or as a waterproofing material or below-grade surfaces such as:

- Swimming Pools
- Concrete Ponds

Make sure that a test for compatibility is performed when sealing surfaces that have been treated with a curing membrane or sealer other than Super Stone® Concentrated Concrete Sealer. Due to the degree of varying surfaces, application of this sealer is at the installer's discretion.

APPLICABLE STANDARDS

Product Appearance and Odor: Clear Liquid with Aromatic Odor

Application Temperature: 35° -110°F

Viscosity: 26, 900 centipoises

Solids by Volume: 47.97%

Weight by Solids: 53.5%

Specify Gravity: 0.98

Gloss: 91 @ 60° angle

Flash Point: 100° F (TCC)

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended. Avoid breathing vapor for prolonged periods of time and use gloves to avoid repeated contact with the skin. Do not use near fire or flame. Do not smoke during application and drying periods. In case of fire, use CO2 or dry chemical extinguisher. Do not use water spray.

Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes and seek immediate medical attention. **Ingestion**-- If swallowed, contact your local poison control or dial 911 immediately. **Skin**-- Wash the affected area thoroughly with soap and water. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If symptoms persist or develop, seek medical attention.

Limited Warranty: Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits.

For Professional Use

DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. OVEREXPOSURE MAY CAUSE CHEMICAL PNEUMONIA, DELAYED PULMONARY EDEMA AND LUNG CANCER IF INHALED, SKIN DRYNESS OR CRACKING, NARCOTIC EFFECTS AND RESPIRATORY IRRITATION.

