

SOLVENT



Super Stone® Solvent is a clear, colorless, flammable high-strength solvent formulated specifically, as a thinner and clean-up material for resin-based compounds with various uses from tool clean-up to thinning down solvent-based sealers.

RECOMMENDED USAGE

- Equipment & Tool Clean-Up
- Thinning Properties for Acrylic & Resin Based Compounds
- Breakdown of Oil, Grease and Tar Build-Up
- Strong Odor
- Troweling Aid for Epoxy Mortars and Clean-Up of Epoxy Equipment and Tools
- Concrete Surface Coding Agent
- Exterior Use Only

STORAGE/SHELF LIFE

When stored in the original, tightly closed container, preventing the accumulation of water, dirt or other contaminants, the shelf life is two years from the date of purchase. Store in cool ventilated place. Protect material from direct sunlight.

PACKAGING

- 1 Gallon
- 5 Gallons
- 55 Gallon Drum

APPLICATION

Super Stone® Solvent requires no premixing, the product is ready for use directly from the container. Solvent can be added to acrylic and epoxy coatings as a thinning agent. Use to clean tools by putting solvent on rag and continually wipe trowel when doing Epoxy Chattanooga. Use solvent to reduce surface temperature by spraying a thin layer on surface immediately before sealing.

SAFETY PRECAUTIONS

Use with adequate ventilation. A (NIOSH) approved respirator is recommended. Avoid breathing vapor for prolonged periods of time and use gloves to avoid repeated contact with the skin. Do not use near fire or flame. Do not smoke during application and drying periods. In case of fire, use water spray, alcohol resistant foam, dry chemical or Carbon Dioxide.

Avoid contact with eyes, skin, and clothing. First Aid: **Eyes**-- In case of eye contact flush right away with large amounts of water for at least 15 minutes and seek medical attention if irritation persists. **Skin**-- Wash the affected area thoroughly with soap and water for at least 15 min. **Inhalation**-- If you experience difficulty breathing, remove yourself from the area to obtain fresh air. If breathing is difficult, give oxygen. **Ingestion**-- Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Rinse out the mouth with water. Get medical attention immediately.

Limited Warranty: *Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Super Stone solely and expressly warrants that this product shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective and this shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach.* NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits. Any installation of Super Stone products which fails to conform with such installation information or instructions shall void this warranty. Buyer shall be solely responsible for determining the suitability of Super Stone's products for the Buyer's intended purposes.

FOR PROFESSIONAL USE

WARNING! EXTREMELY FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN. KEEP AWAY FROM HEAT, HOT SURFACES, OPEN FLAMES, SPARKS. MAY CAUSE SKIN IRRITATION, GENETIC DEFECTS, CANCER, DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTER AIRWAYS. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

