

# STRIP IT OFF S/R

Super Stone® Strip It Off S/R is a Sprayable, professional high-performance paint/coatings stripper. A non-hazardous, water based, ultra-low V.O.C. stripper that can be used for interior and exterior applications. Super Stone® Strip It Off S/R will aid in the removal of solvent-based acrylic, water based, urethane, varnish, lacquer, adhesives, and other floor finish build-ups and is easy to use.

## RECOMMENDED USAGE

- |  |   |
|--|---|
| <ul style="list-style-type: none"><li>• Brick/Pavers/Clay Pavers</li><li>• Concrete/Masonry</li><li>• Natural Stone</li><li>• Plaster / Stucco</li><li>• Pool Deck/ Driveway's</li></ul> | <ul style="list-style-type: none"><li>• Tiles</li><li>• Other Masonry Surfaces</li><li>• Outdoors</li></ul> |
|--|---|

## COVERAGE

Coverage will vary due to type of coating/product being removed, temperature, and application methods.

1 Gallon Covers Approximately 50-100 ft<sup>2</sup>

5 Gallons Cover Approximately 250-500 ft<sup>2</sup>

## STORAGE/SHELF LIFE

When stored in the original, tightly closed container, preventing the accumulation of water, dirt or other contaminants, the shelf life is one year. Store in cool ventilated place. Protect material from direct sunlight.

## PREPARATION

Shake well before use. Test an area to determine effects and dwell time before use. Always work in a small, manageable area. Pre-clean area and allow to dry prior to application. Protect all plants and vegetation. Mask off all surfaces you do not want Strip It Off S/R to come in contact with. When applying with a sprayer in cool weather (50°-70° F) warm Super Stone® Strip It Off S/R to a minimum of 75° F. Note: Place bucket in the sun prior to application. When applying in warm or hot weather above (100° F) store product in a cool shaded area.

## APPLICATION

Shake well before use. Do not dilute. Apply Strip It Off S/R liberally ( do not apply thin) to a dry clean surface with a pump up sprayer, (recommended 1-2 Gal maximum size) brush, or roller and allow to dwell a minimum of 30 minutes. When using a plastic type pump sprayer, it is recommended to use a cone tip (Do not use a metal type sprayer, plastic only). Depending on temperature, type of coating, and number of coats, dwell time will vary from 30 minutes to 12 hours. Do not allow product to dry before removing coating. If longer dwell time is needed keep product wet by applying more Strip It Off S/R or cover with visqueen. Strip It Off S/R goes on white and once it turns clear coating is usually ready to be removed. Scrape off or pressure wash with a surface cleaner (and or) a turbo tip to

remove. Dispose of residue according to local, state, and federal regulations. Once coating is removed be sure to clean the surface area of all remaining residues by scrubbing, rinsing, power washing etc. Some coatings may require additional dwell time and or applications.

## CLEAN-UP

Clean up all equipment with soap and water immediately after use.

## SAFETY PRECAUTIONS

**KEEP OUT OF REACH OF CHILDREN.** Avoid contact with skin and eyes. Wear safety goggles and gloves when using. Do not take internally. Keep container closed when not in use.

**IF INGESTED:** Rinse mouth with water and give one glass of water to the person if conscious. Seek medical attention immediately. **IF CONTACT WITH EYES:** Immediately flush eyes with water for 20 minutes. Remove contact lenses if present and easy to do and continue to flush with water. Seek immediate medical attention. **IF ON SKIN:** Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash all contaminated clothing thoroughly.

***Limited Warranty: Since no control is exercised over product use, Super Stone® only warrants that this product is of consistent quality within manufacturing tolerances. Super Stone solely and expressly warrants that this product shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of the portion of the material proved to be defective and this shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. NO OTHER ORAL OR WRITTEN REPRESENTATION OR STATEMENT OF ANY KIND, EXPRESSED OR IMPLIED, NOW OR HEREAFTER MADE IS AUTHORIZED OR WARRANTED BY SUPER STONE, INCLUDING THOSE OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Super Stone will not be liable for special, incidental or consequential damages, including for delays or lost profits. Any installation of Super Stone products which fails to conform with such installation information or instructions shall void this warranty. Buyer shall be solely responsible for determining the suitability of Super Stone's products for the Buyer's intended purposes.***

FOR PROFESSIONAL USE

